



Enjoy Birds More Limited

Product Data Sheet

Bird Table Camera

Product Code C11

Item	Description
Camera Unit	<p>Camera Housing containing Infra Red lighting array, ambient light sensor and lighting controller, colour video camera, audio system and transmitter.</p> <p>Camera: PAL colour CCD video camera assembly with high sensitivity to visible and infra red spectrum, 420 line, 512 x 582 effective pixels, focal range approx 200mm to infinity. Audio system with microphone.</p> <p>Transmission system operating at (nominal) 10mW output level in 2.4GHz band with externally mounted omnidirectional antenna. Set to 1 of 4 different frequency channels. Nominal range 100 metres.</p> <p>Video and audio outputs through Phono sockets, and DC supply through low voltage power connector.</p> <p>Mounted in sealed surface coated metal/glass housing exceeding the IP67 standard suitable for immersion in unpressurised water to a depth of 1 metre. Video/audio/power cable 2.5 metres (nominal) long. External adjustable camera bracket. Operating temperature range: -20°C to +70°C.</p>
Offset Mounting Bracket and Camera Anciliaries	<p>Wooden strut offset bracket approximately 690mm long, designed for mounting at 45° to upright. Fixings at top for camera bracket, and at bottom for mounting with woodscrews to post of bird table or with clamp (included) onto upright of bird feeder. Suitable for clamping to circular section upright between 15mm and 30mm diameter. Strut and clamp made from softwood and exterior grade plywood, certified from mixed sources (product group from well-managed forests and recycled wood) in accordance with the rules of the Forest Stewardship Council (Enjoy Birds More Limited is certified under SW-COC-005535 EK).</p> <p>Screws, bolts and washers provided for mounting camera and bracket. 3 reusable cable ties for securing cable to tie and upright. Hex key for adjustment of camera bracket.</p> <p>Battery Box with on/off switch and 1.6 metre cable, including battery holder for 4 x "D" batteries. Plastic weather resistant cover for cable join, complete with 4 cable ties. Mains (240V) power supply unit (interior use only) with PP3 connector and 1.2 metre (approx) low voltage cable (suitable for external use).</p>
Video/Audio Receiver	<p>Video and audio receiver operating in 2.4GHz band, switch selectable to 1 of 4 different frequency channels. Mains (240V) power supply unit. Video and audio output.</p>
Video/Audio Cable	<p>1.6 metre (approx) long cable with colour coded video and audio phono (RCA) plugs at each end, suitable for connection between Receiver and TV / VCR / Video to USB Converter.</p>